Material Safety Data Sheet





Revision Number: 003.0

	1. PRODUCT AND CO	OMPANY IDENT	IFICATION
Product name:	392 Structural Adhesive Heat/Activator Cure	r IDH number:	232853
Product type:	Acrylic Adhesive	ltem number: Region:	39205 United States
Company address: Henkel Corporation		Contact information Telephone: 860.571.	n: .5100
1001 Trout Brook Cro Rocky Hill, Connecticu		Emergency telephone: 860.571.5100 Internet: www.henkelna.com	
	2. HAZARDS		ON
	EMERGENCY		
Physical state: Color: Odor:	Liquid Beige, Dark Amber Sharp	<u>HMIS:</u> HEALTH: FLAMMABIL PHYSICAL H Personal Pro	IAZARD: 1
WARNIN	G: COMBUSTIBLE LIQUI CAUSES EYE AND SK MAY CAUSE ALLERG MAY CAUSE RESPIRA	D AND VAPOR. (IN IRRITATION. IC SKIN REACTIC	DN.
Relevant routes of e	xposure: Skin, Inhalation, Eyes		
Potential Health Effe	<u>cts</u>		
Inhalatio Skin con Eye cont Ingestior	ttact: Causes skin irritation. N tact: Vapors may irritate eye	May cause allergic skin es. Contact with eyes w	
Existing conditions a exposure:	aggravated by Eye, skin, and respirate	ory disorders.	
	This material is conside 1910.1200).	ered hazardous by the (OSHA Hazard Communication Standard (29 CFF

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Polyurethane methacrylate resin	Proprietary	30 - 60	
2-Hydroxyethyl methacrylate	868-77-9	10 - 30	
Isobornyl acrylate	5888-33-5	10 - 30	
Methacrylic acid	79-41-4	5 - 10	
Treated fumed silica	67762-90-7	5 - 10	
Tert-butyl perbenzoate	614-45-9	1 - 5	
Maleic acid	110-16-7	1 - 5	
Saccharin	81-07-2	1 - 5	

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.	
Skin contact:	Immediately wash skin thoroughly with soap and water. Remove contamina clothing and footwear. Wash clothing before reuse. If symptoms develop an persist, get medical attention.	
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at leas 15 minutes, holding eyelids open all the time. Get medical attention.	
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Keep individual calm. Get medical attention.	
5. I	FIRE FIGHTING MEASURES	
Flash point:	77.2 °C (170.96 °F) Tagliabue closed cup	
Autoignition temperature:	Not available	
Flammable/Explosive limits - lower:	Not available	
Flammable/Explosive limits - upper:	Not available	
Extinguishing media:	Foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear.	
Unusual fire or explosion hazards:	None expected.	
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic	

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal.

7.	HANDLING AND	STORAGE

Handling:	Use only with adequate ventilation. Keep away from heat, spark and flame. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow.
Storage:	For safe storage, store at or below 38 °C (100.4 °F) Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyurethane methacrylate resin	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Isobornyl acrylate	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Tert-butyl perbenzoate	None	None	None	None
Maleic acid	None	None	None	None
Saccharin	None	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Skin protection:

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Boiling point/range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Liquid Beige, Dark Amber Sharp Not available Not applicable < 10 mm Hg (27 °C (80.6 °F)) > 149 °C (> 300.2 °F) Not available 1.16 Not available 77.2 °C (170.96 °F) Tagliabue closed cup Not available Not available Not available Not available Slight Not available 2.22 %; 21.15 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic vapours. Isocyanates. Hydrogen cyanide. Amines.
Incompatible materials:	Strong oxidizing agents. Reducing agents. Acids. Bases. Peroxides. Amines. Strong alkalis. Reactive metals. Oxygen scavengers. Free radical initiators.
Conditions to avoid:	Store away from incompatible materials. Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyurethane methacrylate resin	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Isobornyl acrylate	No	No	No
Methacrylic acid	No	No	No
Treated fumed silica	No	No	No
Tert-butyl perbenzoate	No	No	No
Maleic acid	No	No	No
Saccharin	No	No	No

Hazardous components	Health Effects/Target Organs	
Polyurethane methacrylate resin	Irritant, Allergen	
2-Hydroxyethyl methacrylate	Irritant, Allergen	
Isobornyl acrylate	Irritant, Allergen	
Methacrylic acid	Corrosive, Irritant, Allergen	
Treated fumed silica Irritant		
Tert-butyl perbenzoate	Central nervous system, Irritant, Mutagen	
Aleic acid Irritant, Kidney		
Saccharin	No Target Organs	

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

Not regulated

None

None

None

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Combustible liquid, n.o.s. (Methylacrylic acid, stabilized, tert-Butyl perbenzoate)
Hazard class or division:	Combustible Liquid
Identification number:	NA 1993
Packing group:	
DOT Reportable quantity:	Saccharin

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12(b) Export Notification: None above reporting de minimus CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire CERCLA/SARA 313: None above reporting de minimus **CERCLA Reportable quantity:** Saccharin (CAS# 81-07-2) 100 lbs. (45.4 kg) This product contains a chemical known in the State of California to cause cancer. California Proposition 65: Canada Regulatory Information **CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List. WHMIS hazard class: B.3. D.2.B **16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format. 1,2,3,4,5,8,9,10,11, and 15

Prepared by: Jennifer Glieco, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.