

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

1 Identification of substance

· **Product details**

· **Trade name:** *D-530L*

· **Manufacturer/Supplier:** EFTEC AG Hofstrasse 31 CH-8590 Romanshorn, Switzerland

· **Information department:** +41(0)71 466 43 00 Customer Support Laboratory

· **Emergency information:** +41(0)1 251 51 51 Swiss Toxicological Information Centre

2 Composition/Data on components

· **Chemical characterization**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

78-93-3	butanone	25-50%
123-86-4	n-butyl acetate	10-25%
28182-81-2	Aliphatisches Polyisocyanat	2.5-10%
872-50-4	N-methyl-2-pyrrolidone	£ 2.5%
4420-74-0	3-trimethoxysilylpropane-1-thiol	£ 2.5%

3 Hazards identification

· **Hazard description:**

Irritant

Highly flammable

· **Canadian Hazard Symbols**



· **Information pertaining to particular dangers for man and environment:**

Highly flammable.

Irritating to eyes.

May cause sensitization by skin contact.

Contains isocyanates. See information supplied by the manufacturer.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

(Contd. on page 2)

- USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

4 First aid measures

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:**

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 2)

- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Class according to regulation on flammable liquids:** A I

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

78-93-3 butanone

PEL	590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
BEI	

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

1333-86-4 Carbon black

PEL	3.5 mg/m ³
REL	3.5* mg/m ³ *0.1 in presence of PAHs
TLV	3.5 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 3)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· Form:	Liquid
· Color:	Black
· Odor:	Characteristic
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79°C (174°F)
· Flash point:	-4°C (25°F)
· Ignition temperature:	370°C (698°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
· Vapor pressure at 20°C (68°F):	105 hPa
· Density:	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	23.1 %
· Solids content:	76.9 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 4)

- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant.

12 Ecological information

- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1993
- **Packing group:** II
- **Proper shipping name (technical name):** Flammable liquid, n.o.s., ethyl methyl ketone (Methyl ethyl ketone)
- **Label** 3

- **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 Flammable liquids
- **Item:** 3b
- **Danger code (Kemler):** 33
- **UN-Number:** 1993

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 5)

· **Description of goods:** 1993 Flammable liquid, n.o.s., ethyl methyl ketone (Methyl ethyl ketone)

· **Maritime transport IMDG:**



· **IMDG Class:** 3.2
 · **Page:** 3230
 · **UN Number:** 1993
 · **Label** 3
 · **Packaging group:** II
 · **EMS Number:** 3-07
 · **MFAG:** 310
 · **Marine pollutant:** No
 · **Propper shipping name:** Flammable liquid, n.o.s., ethyl methyl ketone (Methyl ethyl ketone)

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1993
 · **Label** 3
 · **Packaging group:** II
 · **Propper shipping name:** Flammable liquid, n.o.s., ethyl methyl ketone (Methyl ethyl ketone)

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

78-93-3 butanone

872-50-4 N-methyl-2-pyrrolidone

1330-20-7 xylene (mix)

· **TSCA (Toxic Substances Control Act):**

78-93-3 butanone

123-86-4 n-butyl acetate

1333-86-4 Carbon black

872-50-4 N-methyl-2-pyrrolidone

4420-74-0 3-trimethoxysilylpropane-1-thiol

1330-20-7 xylene (mix)

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 6)

· Proposition 65**· Chemicals known to cause cancer:**

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· Cancerogenity categories**· EPA (Environmental Protection Agency)**

78-93-3 butanone D

1330-20-7 xylene (mix) D

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black 2B

1330-20-7 xylene (mix) 3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1333-86-4 Carbon black A4

1330-20-7 xylene (mix) A4

· MAK (German Maximum Workplace Concentration)

1333-86-4 Carbon black 3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:Irritant
Highly flammable**· Hazard-determining components of labelling:**

Aliphatisches Polyisocyanat

· Risk phrases:

Highly flammable.

Irritating to eyes.

May cause sensitization by skin contact.

· Safety phrases:

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Avoid contact with skin and eyes.

Wear suitable gloves.

(Contd. on page 8)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 05/21/2002

Reviewed on 05/13/2002

Trade name: D-530L

(Contd. of page 7)

This material and its container must be disposed of as hazardous waste.

· Special labeling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Classification according to VbF: A I

· Technical instructions (air):

Class	Share in %
II	£ 2,5
III	50-100

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Customer Support Laboratory

· Contact: H. Perler

USA