

# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, and Canadian WHMIS Standards

## PART I *What is the material and what do I need to know in an emergency?*

### 1. PRODUCT IDENTIFICATION

**TRADE NAME:** OETECH PIT POLISH  
**PRODUCT CODE:** OETPITPOLISH  
**PRODUCT USE:** Windscreen Repair  
**U.N. NUMBER:** Not Applicable  
**U.N. DANGEROUS GOODS CLASS/SUBSIDIARY RISK:** Not Applicable  
**U.S./DISTRIBUTOR'S NAME:** Pilkington North America  
**ADDRESS:** 3440 Centerpoint Drive  
Grove City, OH 43123  
(419) 247 3731  
**U.S. BUSINESS PHONE:** (800) 255 3924 (in transport)  
**U.S. EMERGENCY PHONE:** (800) 424 9300 (in use)  
**MEXICO DISTRIBUTOR'S NAME:** Pilkington Mexico  
**ADDRESS:** Calzada de la Naranja No. 154  
Naucalpan, Estado de México 53370  
MEXICO  
**BUSINESS NUMBER:** 011 52 55 5357 0574  
**EMERGENCY NUMBER:** 011 52 55 5357 0574  
**DATE OF PREPARATION:** January 28, 2010

### 2. HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW:** This product is an opaque, tan liquid with a slight, solvent odor. **Health Hazards:** This product may mildly irritate contaminated tissue, especially upon prolonged exposure. Inhalation of high concentrations of vapors can cause central nervous system depression (e.g., dizziness, headaches, and nausea). This product contains a suspect carcinogen. This product may contain Crystalline Silica, which is known to cause cancer by inhalation. If this product is used in a manner that creates dust, use of respiratory protection is required. **Flammability Hazards:** This product must be substantially preheated before ignition can occur. In the event of a fire, the components of this product may decompose to release irritating vapors and toxic gases (e.g., carbon dioxide, and carbon monoxide). **Reactivity Hazards:** This product is not reactive. **Environmental Hazards:** Releases of this product to the environment, especially in large quantity, may result in environmental damage. **Emergency Recommendations:** Emergency responders must wear personal protective equipment suitable for the situation to which they are responding.

### 3. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	EINECS #	% w/v
Crystalline Silicas	14464-46-1	238-455-4	1.0 – 5.0%
	14808-60-7	238-878-4	0.1 – 1.0%
Polydimethyl Siloxane	63148-62-9	Unlisted	4-8%
Morpholine	110-91-8	203-815-1	1.0-5.0%
Oleic Acid	112-80-1	204-007-1	1.0-5.0%
Amorphous Silicas/ Diatomaceous Earths	68855-54-9	272-489-0	5.0-10.0%
	61790-53-2	310-127-6	1.0 – 5.0%
Odorless Mineral Spirits	64742-48-9	265-150-3	7.0-13.0%
Water and other components. Each of the other components is present in less than 1 percent concentration (or 0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).			Balance

## **PART II**    *What should I do if a hazardous situation occurs?*

### **4. FIRST-AID MEASURES**

Contaminated individuals should be taken for medical attention if they feel unwell or if adverse effects occur. Take copy of label and MSDS to physician or health professional with contaminated individual.

**SKIN EXPOSURE:** If this material contaminates the skin, begin decontamination with running water. Recommended flushing is for 15 minutes if any sign of skin irritation develops. Contaminated individual should seek immediate medical attention if any adverse exposure symptoms develop.

**EYE EXPOSURE:** If this product enters the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open eyelids. Have contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Do not interrupt flushing. Contaminated individual must seek medical attention.

**INHALATION:** If this product is inhaled, remove contaminated individual to fresh air.

**INGESTION:** If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING, unless directed by medical personnel. If victim is conscious, rinse mouth with water immediately. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Skin disorders, respiratory conditions, and central nervous system conditions may be aggravated by prolonged overexposure to this product.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and eliminate overexposure.

### **5. FIRE-FIGHTING MEASURES**

**FLASH POINT (Pensky-Martens Closed Tester):** > 93.3°C (> 200°F)

**AUTOIGNITION TEMPERATURE:** Not established.

**FLAMMABLE LIMITS (in air by volume, %):**

**Lower:** Not established.      **Upper:** Not established.

**FIRE EXTINGUISHING MATERIALS:** Use extinguishing material suitable to the surrounding fire.

**Water Spray:** YES

**Carbon Dioxide:** YES

**Foam:** YES

**Dry Chemical:** YES

**Halon:** YES


**Other:** Any "ABC" Class

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** This product must be substantially preheated before ignition to occur. When involved in a fire, this material may decompose and produce irritating vapors and toxic gases (including silicon compounds, nitrogen oxides, carbon dioxide, and carbon monoxide).

**Explosion Sensitivity to Mechanical Impact:** Not applicable.

**Explosion Sensitivity to Static Discharge:** Not applicable.

**SPECIAL FIRE-FIGHTING PROCEDURES:** As with all chemical products, structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment when responding to fires involving this product.



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate  
3 = Serious 4 = Severe

### **6. ACCIDENTAL RELEASE MEASURES**

**RELEASE RESPONSE:** In case of a release, clear the affected area and respond with trained personnel. Uncontrolled, non-incident, releases require response by appropriately trained personnel in proper personal protective equipment, using pre-planned procedures. Wear neoprene or other chemically resistant gloves for incidental releases (e.g., one 15 mL bottle). Larger releases (e.g., rupture of a process container or several bottles in which one gallon of this material is released) should be responded to in gloves, goggles, and appropriate body protection. An air-purifying respirator with an organic vapor cartridge must be worn during spill responses in which excessive vapors are generated or if the area of the release is poorly ventilated. In the event of a non-incident release in which the material is reacting with other substances, or when the oxygen level is below 19.5% or is unknown, minimum Personal Protective Equipment should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus. Absorb spilled liquid with polypads or other suitable absorbent materials. Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. Dispose of in accordance with international, U.S. Federal, State, and local hazardous waste disposal regulations (see Section 13, Disposal Considerations).

## PART III *How can I prevent hazardous situations from occurring?*

### 7. HANDLING and STORAGE

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this product IN YOU. Wash thoroughly after using this material. Avoid breathing vapor. Do not eat, smoke, apply cosmetics, or drink while handling this material. If this product is used in a manner that can create residual dust from the product (such as application of product with a mechanical polishing wheel), adequate respiratory protection from possible crystalline dust must be used.

**STORAGE AND HANDLING PRACTICES:** All employees who handle this material should be trained to handle it safely. Open bottles carefully. Empty containers may contain residual material and should be handled with care. Store this product in a cool, dry location, away from direct sunlight, sources of intense heat. Store away from incompatible chemicals (see Section 10, Stability and Reactivity). Inspect all incoming containers before storage to ensure they are properly labeled and not damaged.

**SPECIFIC USE(S):** This product is used for vehicle windshield repair. Follow all industry standards for use of this product.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely.

### 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** None normally needed under typical circumstances of use. Local exhaust may be necessary under some usage and handling situations. Prudent practice is to ensure eyewash/safety shower stations are available near areas where this product is used.

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							OTHER mg/m <sup>3</sup>
		ACGIH-TLV		OSHA-PEL		NIOSH			
		TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	IDLH mg/m <sup>3</sup>	
Crystalline Silicas	14808-60-7 14464-46-1	0.05 (respirable fraction)  NIC = 0.025 (respirable fraction)	NE	30 mg/m <sup>3</sup> * (total dust) %SiO <sub>2</sub> + 2 30 mppcf or 10 mg/m <sup>3</sup> ** %SiO <sub>2</sub> + 5 %SiO <sub>2</sub> + 2 * Total Dust ** Respirable Dust		0.05 (respirable dust)	NE	NE	DFG MAK: Respirable fraction Carcinogen: IARC-1, MAK-1, NIOSH-Ca, NTP-K, TLV-A2
Odorless Mineral Spirits	64742-48-9	NE	NE	NE	NE	NE	NE	NE	Novus Inc. Recommendation TWA = 500 ppm
Amorphous Silicas/ Diatomaceous Earths	68855-54-9 61790-53-2	10 (Inhalable Particulates)  3 (Respirable Particulates)		20 mppcf or 80 mg/m <sup>3</sup> %SiO <sub>2</sub> 6 mg/m <sup>3</sup> (Vacated 1989 PEL)		6	NE	3000	DFG MAK: TWA = 0.3 (respirable fraction); 4 (Inhalable Fraction) DFG MAK Pregnancy Risk Group: C Carcinogen: IARC-3
Polydimethyl Siloxane	63148-62-9	NE	NE	NE	NE	NE	NE	NE	NE
Morpholine	110-91-8	71 (skin)	skin	70 (skin)	skin	70 (skin)	105 (skin)	1400 ppm (Based on LEL)	DFG MAKs: TWA = 36 PEAK = 2•MAK 15 min., momentary value, 1-hr interval Carcinogen: IARC-3, TLV-A4
Oleic Acid	112-80-1	NE	NE	NE	NE	NE	NE	NE	NE
Water and other components. Each of the other components is present in less than 1 percent concentration (or 0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).	None of the other components of this product contribute significant, additional, hazards at the concentrations present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian Workplace Hazardous Materials Identification System Standards (CPR 4) and European Community Standards (Commission Directive 93/112/EEC).								

NE = Not Established. NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-1998 format.

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION, continued

**INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS:** In addition to the exposure limit values cited above, other exposure limits have been established by various countries for the components of this mixture, as follows (no listing for a component indicates no values are available).

### **CRYSTALLINE SILICA:**

Austria: MAK = 0.15 mg/m<sup>3</sup>, JAN 1999  
Belgium: TWA = 0.1 mg/m<sup>3</sup>, JAN 1993  
Finland: TWA = 0.2 mg/m<sup>3</sup>, JAN 1999  
France: VME = 10/(X+2), JAN 1999  
Germany: MAK = 0.15 mg/m<sup>3</sup>, JAN 1999  
The Netherlands: MAC-TGG = 0.075 mg/m<sup>3</sup>, JAN 1999  
Norway: TWA = 0.1 mg/m<sup>3</sup> (resp. dust), JAN 1999  
Norway: TWA = 0.3 mg/m<sup>3</sup> (total dust), JAN 1999  
Russia :STEL = 14 mg/m<sup>3</sup>, JAN 1993  
Sweden: NGV = 0.1 mg/m<sup>3</sup> (resp. dust), JAN 1999  
Switzerland: MAK-W = 0.15 mg/m<sup>3</sup>, JAN 1999

### **DIATOMACEOUS EARTH:**

Austria: MAK = 4 mg/m<sup>3</sup>, JAN 1999  
Germany: MAK = 4 mg/m<sup>3</sup>, JAN 1999  
Norway: TWA = 1.5 mg/m<sup>3</sup> (resp. dust), JAN 1999  
Switzerland: MAK-W = 4 mg/m<sup>3</sup>, JAN 1999  
Thailand: TWA = 80 mg/m<sup>3</sup>, JAN 1993  
United Kingdom: TWA = 6 mg/m<sup>3</sup>, total inhalable dust, SEP 2000  
United Kingdom: TWA = 1.2 mg/m<sup>3</sup>, respirable dust, SEP 2000  
In Bulgaria, check ACGIH TLV

### **MORPHOLINE:**

Austria: MAK = 20 ppm (70 mg/m<sup>3</sup>), Skin, JAN 1999  
Belgium: TWA = 20 ppm (71 mg/m<sup>3</sup>), STEL = 30 ppm, Skin JAN1999  
Denmark: TWA = 20 ppm (70 mg/m<sup>3</sup>), Skin, JAN 1999  
Finland: TWA = 20 ppm (70 mg/m<sup>3</sup>), STEL = 30 ppm (105 mg/m<sup>3</sup>), Skin, JAN 1999  
France: VME = 20 ppm (70 mg/m<sup>3</sup>), VLE = 30 ppm (105 mg/m<sup>3</sup>), JAN 1999  
Germany: MAK = 20 ppm (70 mg/m<sup>3</sup>), Skin, JAN 1999  
Hungary: STEL = 10 mg/m<sup>3</sup>, Skin, JAN 1993  
Norway: TWA = 20ppm (70 mg/m<sup>3</sup>), JAN 1999  
Poland: MAC (TWA) = 70 mg/m<sup>3</sup>, MAC(STEL) 100 mg/m<sup>3</sup>, JAN1999  
Russia :TWA = 0.5 mg/m<sup>3</sup>, STEL = 1.5 mg/m<sup>3</sup>, Skin, JAN1993  
Sweden: NGV = 20 ppm (70 mg/m<sup>3</sup>), KTV 30 ppm (110 mg/m<sup>3</sup>), Skin, JAN 1999  
Switzerland: MAK-W = 20 ppm (70 mg/m<sup>3</sup>), KZG-W = 40 ppm (140 mg/m<sup>3</sup>), Skin, JAN 1999  
United Kingdom: TWA = 20 ppm (72 mg/m<sup>3</sup>), STEL 30 ppm, Skin, SEP 2000  
In Bulgaria, check ACGIH TLV

**RESPIRATORY PROTECTION:** None normally needed under typical circumstances of use. Maintain airborne contaminant concentrations below guidelines listed above if applicable. If respiratory protection is needed, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent U.S. State standards. An air-purifying respirator with an organic vapor cartridge is recommended for situations in which excessive vapors are generated or during operations in poorly ventilated areas. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998). If use of this product creates residual dust, the following NIOSH respiratory protection guidelines should be used.

### CRYSTALLINE SILICA

#### CONCENTRATION RESPIRATORY PROTECTION

Up to 0.5 mg/m<sup>3</sup>: Any Air-Purifying Respirator with a high-efficiency particulate filter  
Up to 1.25 mg/m<sup>3</sup>: Any Powered, Air-Purifying Respirator (PAPR) with a high-efficiency particulate filter, or any Supplied-Air Respirator (SAR) operated in a continuous-flow mode.  
Up to 2.5 mg/m<sup>3</sup>: Any Air-Purifying, Full-Facepiece Respirator with a high-efficiency particulate filter, or any PAPR with a tight-fitting facepiece and a high-efficiency particulate filter.  
Up to 25 mg/m<sup>3</sup>: Any SAR operated in a pressure-demand or other positive-pressure mode.  
Emergency or Planned Entry into Unknown Concentrations or IDLH Conditions: Any Self-Contained Breathing Apparatus (SCBA) that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode, or any SAR that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary Self-Contained Breathing Apparatus (SCBA) operated in pressure-demand or other positive-pressure mode.  
Escape: Any Air-Purifying, Full-Facepiece Respirator with a high-efficiency particulate filter, or any appropriate escape-type, SCBA.

**EYE PROTECTION:** Splash goggles or safety glasses may be worn if operations can generate mists of this product. If necessary, refer to U.S. OSHA 29 CFR 1910.133 for further information.

**HAND PROTECTION:** Natural rubber, neoprene, or nitrile rubber gloves. If necessary, refer to U.S. OSHA 29 CFR 1910.138.

**BODY PROTECTION:** None normally needed under typical circumstances of use. If necessary, use body protection appropriate for task (e.g., Tyvek suit, rubber apron). If necessary, refer appropriate Standards of Canada, the European Standard CEN/TR 15419:2006 for further information. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use protection as described in U.S. OSHA 29 CFR 1910.136 or Canadian CSA Standard Z195-M1984, *Protective Footwear*.

## 9. PHYSICAL and CHEMICAL PROPERTIES

RELATIVE VAPOR DENSITY (air = 1): > 1.0

SPECIFIC GRAVITY (water = 1): 1.01

SOLUBILITY IN WATER: Soluble.

VAPOR PRESSURE, mm Hg @ 50°C: < 75

ODOR THRESHOLD: Not established.

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Not established.

APPEARANCE, ODOR AND COLOR: An opaque, tan liquid with a slight, solvent odor.

HOW TO DETECT THIS SUBSTANCE (warning properties): The appearance and odor are distinguishing characteristics of this product.

EVAPORATION RATE (nBuAc = 1): < 1.0

MELTING/FREEZING POINT: Not established.

BOILING POINT: 80°C (176°F)

pH: Not established.

## 10. STABILITY and REACTIVITY

STABILITY: Stable.

DECOMPOSITION PRODUCTS: The products of thermal decomposition of this material include irritating vapors and toxic gases (e.g., silicon oxides, nitrogen oxides, carbon dioxide, carbon monoxide).

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contact with incompatible chemicals, exposure to elevated temperatures.

## PART IV *Is there any other useful information about this material?*

## 11. TOXICOLOGICAL INFORMATION

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The most significant routes of occupational overexposure are inhalation of vapors and contact with skin and eyes. The symptoms of overexposure to this product are as follows:

INHALATION: Inhalation is not anticipated to be a significant route of overexposure to this product. If mists of this product are inhaled, they can irritate the nose and other tissues of the upper respiratory system. If high concentrations of vapors of this product are inhaled (as may occur if this material is used in a poorly ventilated area), symptoms of central nervous system depression may occur (e.g., headaches, dizziness, nausea). Symptoms are generally alleviated upon breathing fresh air. This product may contain Crystalline Silica, which is known to cause cancer by inhalation. If this product is used in a manner that creates dust (such as application of product with a mechanical polishing wheel), use of respiratory protection is required.

CONTACT WITH SKIN or EYES: Depending on the duration and concentration of overexposure, eye contact can cause irritation and reddening. Skin contact can cause reddening, discomfort, and irritation. Symptoms are generally alleviated upon rinsing.

SKIN ABSORPTION: Skin absorption is a potential route of exposure for the Morpholine component of this product. Symptoms of such exposure would include those listed under "Contact with Eyes or Skin"



INGESTION: Ingestion is not anticipated to be a likely route of exposure to this product. If this material is swallowed, it may cause headache, nausea, and vomiting. Aspiration of this liquid may cause life-threatening lung damage.

INJECTION: Though not anticipated to be a likely route of occupational exposure, injection of this material (via puncture or laceration by a contaminated object) may cause local reddening, tissue swelling, and discomfort in addition to the wound.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in **Lay Terms**.

**ACUTE:** This material may be irritating to the eyes, skin, and mucous membranes. Inhalation of high concentrations of this product's vapors can cause dizziness, headaches, and nausea. If swallowed, aspiration of this liquid may cause life-threatening lung damage.

**CHRONIC:** Repeated skin contact can cause dermatitis (inflammation of the skin, resulting in redness and dryness). The Odorless Mineral Spirits component of this product is suspect carcinogen, although this compound is not listed by any agency tracking carcinogenic potential. This product may contain Crystalline Silica, which is known to cause cancer by inhalation. This is not an anticipated hazard with this product during normal application and use of the product; however, if this product is used in a manner that creates dust (such as application of product with a mechanical polishing wheel), this may be a hazard. See Section 11 (Toxicology Information) for additional information on the components of this product.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD	(BLUE)	1	
FLAMMABILITY HAZARD	(RED)	1	
PHYSICAL HAZARD	(YELLOW)	0	
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate  
3 = Serious 4 = Severe \* = Chronic hazard

**TARGET ORGANS:** ACUTE: Skin, eyes, central nervous system. CHRONIC: Skin

**TOXICITY DATA:** The specific toxicology data available for the components of this product present in greater than 1 percent concentration are presented below:

**SILICA, CRYSTALLINE-QUARTZ:**

LCLo (Inhalation-Human) 300 mg/m<sup>3</sup>/10 years-intermittent: Systemic effects  
TCLo (Inhalation-Human) 16 mppcf/8 hours/17.9 years-intermittent: Pulmonary system effects  
TCLo (Inhalation-Rat) 50 mg/m<sup>3</sup>/6 hours/71 weeks-intermittent: Carcinogenic effects  
TCLo (Inhalation-Rat) 80 mg/m<sup>3</sup>/26 weeks-intermittent: Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis); Blood: changes in spleen; Immunological Including Allergic: decrease in cellular immune  
TCLo (Inhalation-Rat) 108 mg/m<sup>3</sup>/6 hours/3 days-intermittent: Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: phosphatases, Enzyme inhibition, induction, or change in blood or tissue levels: other oxidoreductases, Metabolism (Intermediary): other proteins  
TCLo (Inhalation-Rat) 58 mg/m<sup>3</sup>/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Endocrine: changes in thymus weight; Blood: changes in leukocyte (WBC) count  
TCLo (Inhalation-Mouse) 1475 µg/m<sup>3</sup>/8 hours/21 weeks-intermittent: Lungs, Thorax, or Respiration: other changes  
TCLo (Inhalation-Mouse) 4932 µg/m<sup>3</sup>/24 hours/39 weeks-continuous: Endocrine: changes in spleen weight; Immunological Including Allergic: decrease in humoral immune response  
TCLo (Inhalation-Guinea Pig) 28 mg/m<sup>3</sup>/3 weeks-continuous: Lungs, Thorax, or Respiration: other changes, changes in lung weight; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: other  
TDLo (Intraperitoneal-Rat) 45 mg/kg: Carcinogenic effects  
TDLo (Intratracheal-Rat) 90 mg/kg: Equivocal tumorigenic agent  
TDLo (Intratracheal-Rat) 90 mg/kg: AR  
TDLo (Intratracheal-Rat) 111 mg/kg: Carcinogenic effects  
TDLo (Intratracheal-Rat) 111 mg/kg: AR  
TDLo (Intratracheal-Rat) 100 mg/kg/19 weeks-intermittent: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Lungs, Thorax, or Respiration: tumors  
TDLo (Intraleural-Rat) 90 mg/kg: Carcinogenic effects  
TDLo (Intraleural-Hamster) 83 mg/kg: Tumorigenic: neoplastic by RTECS criteria, tumors at site of application  
**SILICA, CRYSTALLINE-QUARTZ (continued):**  
TDLo (Implant-Rat) 900 mg/kg: Neoplastic effects  
TDLo (Implant-Mouse) 4000 mg/kg: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Kidney, Ureter, Bladder: tumors  
TDLo (Implant-Mouse) 4000 mg/kg: Equivocal tumorigenic agent  
TDLo (Intravenous-Rat) 90 mg/kg: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Blood: lymphoma, including Hodgkin's disease  
TD (Intraperitoneal-Rat) 90 mg/kg/4 weeks-intermittent: Equivocal tumorigenic agent  
TD (Intraperitoneal-Rat) 450 mg/kg/4 weeks-intermittent: Neoplastic effects

TD (Implant-Rat) 4554 mg/kg: Equivocal tumorigenic agent  
TD (Intraleural-Rat) 200 mg/kg: Equivocal tumorigenic agent  
TD (Intraleural-Rat) 100 mg/kg: Carcinogenic effects  
TD (Intraleural-Rat) 100 mg/kg: Neoplastic effects  
TD (Intraleural-Rat) 100 mg/kg: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis), tumors  
LDLo (Intravenous-Rat) 90 mg/kg  
LDLo (Intratracheal-Rat) 200 mg/kg  
LDLo (Intravenous-Mouse) 40 mg/kg  
LDLo (Intravenous-Dog, adult) 20 mg/kg  
Micronucleus test (Human-Lung) 40 µg/cm<sup>2</sup>  
Micronucleus test (Hamster-Lung) 160 µg/cm<sup>2</sup>  
**MORPHOLINE:**  
Standard Draize Test (Skin-Rabbit) 995 mg/24  
Open Irritation Test (Skin-Rabbit) 500 mg: Moderate  
Standard Draize Test (Eye-Rabbit) 2 mg: Severe  
LD<sub>50</sub> (Oral-Rat) 1450 mg/kg  
LD<sub>50</sub> (Oral-Mouse) 525 mg/kg: Behavioral: sleep, somnolence (general depressed activity)  
LD<sub>50</sub> (Oral-Mammal-species unspecified) 1220 mg/kg  
LD<sub>50</sub> (Intraperitoneal-Mouse) 413 mg/kg: Reproductive: Paternal Effects: testes, epididymis, sperm duct  
LD<sub>50</sub> (Subcutaneous-Mouse) 458 mg/kg  
LD<sub>50</sub> (Skin-Rabbit) 500 µL/kg  
LC<sub>50</sub> (Inhalation-Rat) 8000 ppm/8 hours  
LC<sub>50</sub> (Inhalation-Mouse) 1320 mg/m<sup>3</sup>/2 hours: Sense Organs and Special Senses (Eye): lachrymation; Behavioral: ataxia; Lungs, Thorax, or Respiration: cyanosis  
LC<sub>50</sub> (Inhalation-Mammal-species unspecified) 12000 mg/m<sup>3</sup>  
LDLo (Unreported-Rat) 1600 mg/kg  
LDLo (Oral-Guinea Pig) 100 mg/kg: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified; Gastrointestinal: ulceration or bleeding from stomach, ulceration or bleeding from small intestine  
TDLo (Oral-Rat) 24 gm/kg/30 days-intermittent: Gastrointestinal: necrotic changes; Kidney, Ureter, Bladder: changes in tubules (including acute renal failure, acute tubular necrosis); Related to Chronic Data: death  
TDLo (Skin-Rabbit) 9 gm/kg/10 days-intermittent: Liver: fatty liver degeneration; Skin and Appendages: primary irritation (after topical exposure); Related to Chronic Data: death  
TDLo (Skin-Guinea Pig) 27 gm/kg/30 days-intermittent: Kidney, Ureter, Bladder: changes in both tubules and glomeruli; Skin and Appendages: primary irritation (after topical exposure); Related to Chronic Data: death  
TDLo (Oral-Guinea Pig) 13500 mg/kg/30 days-intermittent: Gastrointestinal: necrotic changes; Kidney, Ureter, Bladder: changes in tubules (including acute renal failure, acute tubular necrosis); Related to Chronic Data: death  
TCLo (Inhalation-Rat) 250 ppm/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis)  
TCLo (Inhalation-Rat) 70 mg/m<sup>3</sup>/4 hours/17 weeks-intermittent: Vascular: BP lowering

**MORPHOLINE (continued):**

not characterized in autonomic section; Blood: changes in leukocyte (WBC) count  
TCLo (Inhalation-Guinea Pig) 70 mg/m<sup>3</sup>/4 hours/17 weeks-intermittent: Liver: liver function tests impaired; Kidney, Ureter, Bladder: other changes in urine composition  
TDLo (Oral-Mouse) 2560 mg/kg/ years-continuous: Tumorigenic: neoplastic by RTECS criteria; Lungs, Thorax, or Respiration: bronchiogenic carcinoma; Liver: tumors  
Morphological Transformation (Mouse-Fibroblast) 125 mg/L  
Morphological Transformation (Mouse-Lymphocyte) 1 µL/L  
Mutation in Mammalian Somatic Cells (Mouse-Lymphocyte) 1 gm/L  
Sister Chromatid Exchange (Hamster-Ovary) 160 mg/L  
**OLEIC ACID:**  
Standard Draize Test (Eye-Human) 15 mg/3 days-intermittent: Moderate  
Open Irritation Test (Skin-Rabbit, adult) 500 mg: Mild irritation effects  
Standard Draize Test (Eye effects-Rabbit, adult) 100 mg Mild irritation effects  
LD<sub>50</sub> (Oral-Rat) 74 g/kg  
LD<sub>50</sub> (Intravenous-Rat) 2400 mg/kg  
LD<sub>50</sub> (Intravenous-Mouse) 230 mg/kg  
LD<sub>50</sub> (Intraperitoneal-mouse) 282 mg/kg  
TDLo (Subcutaneous-Rabbit, adult) 390 mg/kg/17 weeks-intermittent: Equivocal tumorigenic agent  
Cytogenetic Analysis (Saccharomyces cerevisiae) 100 mg/L  
Cytogenetic Analysis (Hamster-fibroblast) 2500 mg/L  
Unscheduled DNA Synthesis (Mouse-Rectal) 35 mg/kg  
**POLYDIMETHYLSILOXANE:**  
Standard Draize Test (Eye-Rabbit) 100 mg/1 hour: Mild  
Standard Draize Test (Eye-Rabbit) 100 µL/24 hours: Mild  
Standard Draize Test (Skin-Rabbit) 500 µL/24 hours: Mild  
LD<sub>50</sub> (Oral-Rat) > 17 gm/kg: Kidney, Ureter, Bladder: other changes; Nutritional and Gross Metabolic: other changes  
LD<sub>50</sub> (Oral-Rat) > 24 gm/kg: Gastrointestinal: hypermotility, diarrhea  
LD (Oral-Rat) > 50 mL/kg  
LC (Inhalation-Rabbit) > 978 mg/m<sup>3</sup>/7.5 hours  
LD<sub>50</sub> (Skin-Rabbit) > 2,200 mg/kg: Behavioral: food intake (animal); Gastrointestinal: hypermotility, diarrhea; Skin and Appendages: dermatitis, other (after systemic exposure)  
LD (Oral-Rat): > 5 gm/kg  
LD (Oral-Guinea Pig) > 10 gm/kg  
LD (Skin-Rabbit) > 20 mL/kg  
LD (Skin-Rabbit) > 10,200 mg/kg  
LD (Intramuscular-Rat) >1200 µL/kg: Immunological Including Allergic: increase in humoral immune response  
LDLo (Intraperitoneal-Mouse) 16 mL/kg: Gastrointestinal: hypermotility, diarrhea; Immunological Including Allergic: decrease in cellular immune response, decrease in humoral immune response

TDL<sub>o</sub> (Oral-Rat) 1800 mL/kg/26 weeks-continuous: Lungs, Thorax, or Respiration: changes in lung weight; Liver: changes in

**POLYDIMETHYLSILOXANE (continued):**

liver weight; Kidney, Ureter, Bladder: other changes in urine composition TDL<sub>o</sub> (Oral-Rat) 18 mg/kg/28 weeks-intermittent: Liver: changes in liver weight; Endocrine: changes in spleen weight

TDL<sub>o</sub> (Oral-Rat) 227 gm/kg: Sense Organs and Special Senses (Eye): corneal damage; Behavioral: food intake (animal); Blood: changes in serum composition (e.g. TP, bilirubin, cholesterol)

TDL<sub>o</sub> (Subcutaneous-Rat) 10 gm/kg: female 6-15 day(s) after conception: Reproductive: Specific Developmental Abnormalities: musculoskeletal system

TDL<sub>o</sub> (Subcutaneous-Rat) 8 gm/kg: female 15-22 day(s) after conception: Reproductive: Effects on Newborn: stillbirth

TDL<sub>o</sub> (Subcutaneous-Mouse) 120 gm/kg: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Skin and Appendages: tumors

TDL<sub>o</sub> (Subcutaneous-Rabbit) 260 mg/kg: female 6-18 day(s) after conception: Reproductive: Effects on Embryo or Fetus: fetal death, Specific Developmental Abnormalities: body wall

**DIATOMACEOUS EARTH:** No toxicology data are available for this component of the product.

**ODORLESS MINERAL SPIRITS:** No toxicology data are available for this component of the product

**CARCINOGENIC POTENTIAL OF COMPONENTS:** The components of this product are listed by agencies tracking the carcinogenic potential of chemical compounds, as follows:

**Amorphous Silica:** IARC-3 (Unclassifiable as to Carcinogenicity in Humans)

**Crystalline Silica:** ACGIH TLV-A2 (Suspected Human Carcinogen); IARC-1 (Carcinogenic to Humans); MAK-1 (Substances that Cause Cancer in Man and Can Be Assumed to Make a Significant Contribution to Cancer Risk); NIOSH-Ca (Potential Occupational Carcinogen with No Further Categorization); NTP-K (Known to Be a Human Carcinogen)

**Morpholine:** ACGIH TLV-A4 (Not Classifiable as a Human Carcinogen); IARC-3 (Unclassifiable as to Carcinogenicity in Humans)

The remaining components of this product listed in Section 2 are not found on the following lists: FEDERAL OSHA Z LIST, NTP, IARC, and CAL/OSHA.

**IRRITANCY OF PRODUCT:** This product can be mildly irritating to contaminated eyes, skin and mucous membranes.

**SENSITIZATION TO THE PRODUCT:** No components are known to be skin sensitizers with prolonged or repeated overexposure.

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects of the components on the human reproductive system.

**Mutagenicity:** The components of this product are not expected to cause reproductive effects in humans. Mutation data are available for the Morpholine and Oleic Acid components of this product; these data were obtained during clinical studies on specific microorganisms or animal tissues exposed to high doses of this compound. Both positive and negative results have been reported in short-term in-vitro tests for Crystalline Silica using bacteria and cultured mammalian cells.

**Embryotoxicity:** The components of this product are not expected to produce embryotoxic effects in humans.

**Teratogenicity:** The components of this product are not expected to cause teratogenic effects in humans.

**Reproductive Toxicity:** The components of this product are not expected to cause reproductive toxicity effect in humans.

*A **mutagen** is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An **embryotoxin** is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance which interferes in any way with the reproductive process.*

**SYNERGISTIC PRODUCTS:** There is disagreement about whether tobacco smoke increases the severity of the effect of silica dust on respiratory impairment. Simultaneous exposure to known carcinogens, for example, benzo(a)pyrene, can increase the carcinogenicity of crystalline silica. A synergistic effect between smoking and crystalline silica and/or silicosis on risk of lung cancer, is also likely.

**BIOLOGICAL EXPOSURES INDICES (BEIs):** Currently, there are no Biological Exposure Indices (BEIs) determined for any component of this product.

---

## 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**ENVIRONMENTAL STABILITY:** The components of this product are relatively stable under ambient environmental conditions. Additional environmental data are available as follows:

**OLEIC ACID:** Water Solubility = Insoluble; Log  $K_{ow}$  = 7.18; Major Species Threatened: Waterfowl

**MOBILITY:** This product has not been tested for mobility in soil.

**PERSISTENCE AND BIODEGRADABILITY:** This product has not been tested for persistence or biodegradability.

**MORPHOLINE:** Persistence: Biodegrades at moderate rate. Biodegradation: Morpholine was completely degraded microbiologically and 2 organisms isolated, each capable of growth in a simple mineral salts medium with morpholine as the sole source of C, N, and energy. Excess Morpholine is liberated as ammonia. The enzymes responsible for the oxidation of morpholine are inducible. The possible effects of other chemicals in trade wastes containing morpholine on nitrification and morpholine oxidation are described.; Bioconcentration: Because Morpholine is miscible with water and has a measured octanol/water partition coefficient ( $K_{ow}$ ) of 0.14 (2), its tendency to bioconcentrate will be extremely low.; Effect of low concentrations on aquatic life is unknown.

**BIO-ACCUMULATION POTENTIAL:** This product has not been tested for bio-accumulation potential.

**EFFECT OF MATERIAL ON PLANTS or ANIMALS:** This product is not anticipated to have significant, adverse effects on terrestrial plants and animals.

## 12. ECOLOGICAL INFORMATION (Continued)

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** This product is not anticipated to have significant, adverse effects on aquatic plants and animals. Additional aquatic toxicity data are available as follows:

### **MORPHOLINE:**

LC<sub>0</sub> (*Pseudomonas putida* bacteria) 16 hours = 310 mg/L  
EC<sub>10</sub> (*Pseudomonas sp.* bacteria) = >8,700 mg/L  
EC<sub>10</sub> (*Mycobacterium aurum* bacteria) = >5,000 mg/L  
EC<sub>0</sub> (*Microcystis aeruginosa* algae) 8 days = 1.7 mg/L  
EC<sub>0</sub> (*Scenedesmus quadricauda* algae) 7 days = 4.1 mg/L  
EC<sub>0</sub> (*Selenastrum capricornutum* algae) 96 hours = 10 mg/L  
EC<sub>50</sub> (*Selenastrum capricornutum* algae) 96 hours = 28 mg/L  
EC<sub>100</sub> (*Selenastrum capricornutum* algae) 96 hours = 80 mg/L  
NOEC (*Selenastrum capricornutum* algae) 72 hours = 80 mg/L  
LOEC (*Scenedesmus subspicatus* algae) 24-120 hours = 5-50; 5-100 mg/L  
LOEC (*Selenastrum capricornutum* algae) 24-120 hours = 50-100 mg/L  
LOEC (*Chlorella vulgaris* algae) 24-120 hours = 5-100 mg/L  
EC<sub>0</sub> (*Entosiphon sulcatum* protozoa) 72 hours = 12 mg/L  
EC<sub>0</sub> (*Uronema parduczi* Chatton-Lwoff protozoa) = 815 mg/L  
EC<sub>0</sub> (*Daphnia magna* Straus crustacean) 24 hours = 16; 68 mg/L  
EC<sub>50</sub> (*Daphnia magna* Straus crustacean) 24 hours = 100; 101; 119 mg/L  
EC<sub>100</sub> (*Daphnia magna* Straus crustacean) 24 hours = 260; 500 mg/L  
LC<sub>50</sub>,S (*Lepomis macrochirus*) 24 hours = 530 mg/L  
LC<sub>100</sub>,S (*Lepomis macrochirus*) 24 hours = >370 mg/L  
LC<sub>50</sub>,S (*Lepomis macrochirus*) 48 hours = 520 mg/L  
LC<sub>50</sub>,S (*Lepomis macrochirus*) 72 hours = 370 mg/L  
LC<sub>100</sub>,S (*Lepomis macrochirus*) 48 hours = >320 mg/L  
LC<sub>100</sub>,S (*Lepomis macrochirus*) 72 hours = >320 mg/L

### **MORPHOLINE (continued):**

LC<sub>50</sub>,S (*Lepomis macrochirus*) 96 hours = 350 mg/L  
LC<sub>100</sub>,S (*Lepomis macrochirus*) 96 hours = >10 mg/L  
LC<sub>50</sub>,S (*Menidia beryllina*) 24 hours = >560 mg/L  
LC<sub>100</sub>,S (*Menidia beryllina*) 24 hours = >420 mg/L  
LC<sub>50</sub>,S (*Menidia beryllina*) 48 hours = 510 mg/L  
LC<sub>100</sub>,S (*Menidia beryllina*) 48 hours = >420 mg/L  
LC<sub>50</sub>,S (*Menidia beryllina*) 72 hours = 420 mg/L  
LC<sub>100</sub>,S (*Menidia beryllina*) 72 hours = >320 mg/L  
LC<sub>50</sub>,S (*Menidia beryllina*) 96 hours = 380 mg/L  
LC<sub>100</sub>,S (*Menidia beryllina*) 96 hours = >320 mg/L  
LC<sub>50</sub> (*Salmo gairdneri*) 96 hours = 380 mg/L (hard water)  
LC<sub>50</sub> (*Salmo gairdneri*) 96 hours = 20 mg/L (soft water)  
LC<sub>0</sub> (*Tilapia sp.*) 96 hours = 1,000 mg/L  
LC<sub>0</sub> (*Chelon engeli*) 96 hours = 100 mg/L  
LC<sub>100</sub> (*Chelon engeli*) 96 hours = 320 mg/L

### **OLEIC ACID:**

LC<sub>50</sub> (fathead minnow) 1 hour = 1000 mg/L  
LC<sub>50</sub> (fathead minnow) 24 hours = 285 mg/L  
LC<sub>50</sub> (fathead minnow) 48 hours = 252 mg/L  
LC<sub>50</sub> (fathead minnow) 72 hours = 205 mg/L  
LC<sub>50</sub> (fathead minnow) 96 hours = 205 mg/L  
LC<sub>50</sub> (*Oryzias latipes*) 96 hours = 217 mg/L (sodium salt)  
Lethal Dose (goldfish) = 8 mg/L (sodium salt)

---

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS:** It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed of. Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Shipment of wastes must be done with appropriately permitted and registered transporters.

**DISPOSAL CONTAINERS:** Waste materials must be placed in and shipped in appropriate 5-gallon or 55-gallon poly or metal waste pails or drums. Permeable cardboard containers are not appropriate and should not be used. Ensure that any required marking or labeling of the containers be done to all applicable regulations.

**PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING:** Wear proper protective equipment when handling waste materials.

**U.S. EPA WASTE NUMBER:** Not applicable.

---

## 14. TRANSPORTATION INFORMATION

**THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.**

**MARINE POLLUTANT:** The components of this product are not listed as a marine pollutant as per D.O.T. (49 CFR 172.101, Appendix B).

**TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:** This product is NOT considered as Dangerous Goods, per regulations of Transport Canada.

**INTERNATIONAL AIR TRANSPORT ASSOCIATION DESIGNATION:** This product is not considered as dangerous goods, per rules of IATA.

**INTERNATIONAL MARITIME ORGANIZATION (IMO):** This product is not considered as dangerous goods, per rules of the IMO. **Marine Pollutant:** The components of this product are not designated by the IMO to be Marine Pollutants.

---

## 15. REGULATORY INFORMATION

### **U.S. STATE AND FEDERAL REGULATIONS:**

**U.S. SARA REPORTING REQUIREMENTS:** The components of this product are NOT subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

**U.S. CERCLA REPORTABLE QUANTITY (RQ):** Not applicable.

**OTHER U.S. FEDERAL REGULATIONS:** Not applicable.

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):** No component of this product is on the California Proposition 65 lists.



## 15. REGULATORY INFORMATION (Continued)

### U.S. STATE AND FEDERAL REGULATIONS (continued):

U.S. ANSI STANDARD LABELING (Z129.1): **CAUTION!** MAY CAUSE SKIN AND EYE IRRITATION. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. ASPIRATION HAZARD - MAY CAUSE LIFE-THREATENING LUNG DAMAGE IF SWALLOWED. CONTAINS SUSPECT CARCINOGEN. RISK OF CANCER DEPENDS ON CONCENTRATION AND DURATION OF CONTACT. Do not taste or swallow. Do not get on skin or in eyes. Avoid breathing vapor or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Wear gloves and eye protection. **FIRST-AID:** In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes. If inhaled, remove to fresh air. If ingested, do not induce vomiting and get medical attention. Get medical attention if any adverse reaction occurs. **IN CASE OF FIRE:** Use water fog, dry chemical, CO<sub>2</sub>, or "alcohol" foam. **IN CASE OF SPILL:** Absorb spill with inert material and place in suitable container. Consult Material Safety Data Sheet for additional information.

### ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL INVENTORY: The components of this product are listed on the DSL Inventory.

CANADIAN WHMIS IDL DISCLOSURE STATUS: The Amorphous Silica/ Diatomaceous Earth Crystalline Silica, Morpholine and Oleic components of this product have a disclosure level of 1%.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION AGENCY (CEPA) PRIORITY SUBSTANCES LISTS: The components of this product are not on the Priority Substances Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Class D2B (Materials Causing Other Toxic Effects)



---

## 16. OTHER INFORMATION

### ORIGINALLY PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.  
PO Box 3519, La Mesa, CA 91944-3519  
(800) 441-3365

### DATE OF FIRST PREPARATION:

November 25, 1997

### DATE OF PRINTING:

February 2, 2010

### REVISION HISTORY:

February 26, 2002: Addition information on Crystalline Silica.

June 30, 2004: New business address

October 10, 2005: Up-date of MSDS to include current EU format. Review and up-date of exposure limits.

The Material Safety Data Sheet is offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

## DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

**CAS #:** This is the Chemical Abstract Service Number that uniquely identifies each constituent.

**CEILING LEVEL:** The concentration that shall not be exceeded during any part of the working exposure.

**DFG MAK Germ Cell Mutagen Categories:** **1:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens which have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances which have been shown to induce genetic damage in germ cells of human or animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances which are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but which are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

**DFG MAK Pregnancy Risk Group Classification:** **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

**LOQ:** Limit of Quantitation.

**MAK:** Federal Republic of Germany Maximum Concentration Values in the workplace.

**NE:** Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

**NIC:** Notice of Intended Change.

**NIOSH CEILING:** The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

**NIOSH RELs:** NIOSH's Recommended Exposure Limits.

**PEL-Permissible Exposure Limit:** OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

### EXPOSURE LIMITS IN AIR (continued):

**SKIN:** Used when there is a danger of cutaneous absorption.

**STEL-Short Term Exposure Limit:** Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

**TLV-Threshold Limit Value:** An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

**TWA-Time Weighted Average:** Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

**IDLH-Immediately Dangerous to Life and Health:** This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD

**RATINGS:** This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

#### HEALTH HAZARD:

**0 (Minimal Hazard):** No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. PII or Draize = "0". *Eye Irritation:* Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. Draize = "0". *Oral Toxicity LD<sub>50</sub> Rat:* < 5000 mg/kg. *Dermal Toxicity LD<sub>50</sub>Rat or Rabbit:* < 2000 mg/kg. *Inhalation Toxicity 4-hrs LC<sub>50</sub> Rat:* < 20 mg/L.; **1 (Slight Hazard: Minor reversible Injury)** may occur; slightly or mildly irritating. *Skin Irritation:* Slightly or mildly irritating. *Eye Irritation:* Slightly or mildly irritating. *Oral Toxicity LD<sub>50</sub> Rat:* > 500-5000 mg/kg. *Dermal Toxicity LD<sub>50</sub>Rat or Rabbit:* > 1000-2000 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat:* > 2-20 mg/L.; **2 (Moderate Hazard: Temporary or transitory injury may occur. Skin Irritation: Moderately irritating; primary irritant; sensitizer. PII or Draize > 0, < 5. Eye Irritation: Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. Draize > 0, ≤ 25. Oral Toxicity LD<sub>50</sub> Rat: > 50-500 mg/kg. *Dermal Toxicity LD<sub>50</sub>Rat or Rabbit:* > 200-1000 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat:* > 0.5-2 mg/L.); **3 (Serious Hazard: Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. Skin Irritation: Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns, dermal necrosis. PII or Draize > 5-8 with destruction of tissue. Eye Irritation: Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. Oral Toxicity LD<sub>50</sub> Rat: > 1-50 mg/kg. *Dermal Toxicity LD<sub>50</sub>Rat or Rabbit:* > 20-200 mg/kg. *Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat:* > 0.05-0.5 mg/L.); **4 (Severe Hazard: Life-threatening; major or permanent damage may result from single or repeated exposure. Skin Irritation: Not appropriate. Do not rate as a "4", based on skin irritation alone. Eye Irritation: Not appropriate. Do not rate as a "4", based on eye irritation alone. Oral Toxicity LD<sub>50</sub> Rat ≤ 1 mg/kg. Dermal Toxicity LD<sub>50</sub>Rat or Rabbit: ≤ 20 mg/kg. Inhalation Toxicity LC<sub>50</sub> 4-hrs Rat: ≤ 0.05 mg/L).******

## DEFINITIONS OF TERMS (Continued)

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

#### FLAMMABILITY HAZARD:

**0** (Minimal Hazard-Materials that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.); **1** (Slight Hazard-Materials that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, including: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.]; **2** (Moderate Hazard-Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, including: Liquids having a flash-point at or above 37.8°C [100°F]; Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); **3** (Serious Hazard-Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] [e.g. OSHA Class IB and IC]; Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides]); **4** (Severe Hazard-Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] [e.g. OSHA Class IA; Material that ignite spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric].)

#### PHYSICAL HAZARD:

**0** (*Water Reactivity*: Materials that do not react with water. *Organic Peroxides*: Materials that are normally stable, even under fire conditions and will not react with water. *Explosives*: Substances that are Non-Explosive. *Unstable Compressed Gases*: No Rating. *Pyrophorics*: No Rating. *Oxidizers*: No "0" rating allowed. *Unstable Reactives*: Substances that will not polymerize, decompose, condense or self-react.); **1** (*Water Reactivity*: Materials that change or decompose upon exposure to moisture. *Organic Peroxides*: Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. *Explosives*: Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases*: Pressure below OSHA definition. *Pyrophorics*: No Rating. (*Oxidizers*: Packaging Group III; *Solids*: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. *Liquids*: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives*: Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors.); **2** (*Water Reactivity*: Materials that may react violently with water. *Organic Peroxides*: Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water.

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

**2** (continued): *Explosives*: Division 1.4 – Explosive substances where the explosive effect is largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases*: Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics*: No Rating. *Oxidizers*: Packing Group II *Solids*: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. *Liquids*: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Unstable Reactives*: Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature); **3** (*Water Reactivity*: Materials that may form explosive reactions with water. *Organic Peroxides*: Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives*: Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases*: Pressure  $\geq$  514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics*: No Rating. *Oxidizers*: Packing Group I *Solids*: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. *Oxidizers*: *Liquids*: Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives*: Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.); **4** (*Water Reactivity*: Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides*: Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives*: Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases*: No Rating. *Pyrophorics*: Add to the definition of Flammability "4". *Oxidizers*: No "4" rating. *Unstable Reactives*: Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion.)

### NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: **0** (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); **1** (materials that on exposure under fire conditions could cause irritation or minor residual injury); **2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); **3** (materials that can on short exposure could cause serious temporary or residual injury); **4** (materials that under very short exposure could cause death or major residual injury).

FLAMMABILITY HAZARD: **0** Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily.

## DEFINITIONS OF TERMS (Continued)

### NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

**INSTABILITY HAZARD:** **0** Materials that in themselves are normally stable, even under fire conditions. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures.

### FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point** - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. **Autoignition Temperature:** The minimum temperature required to initiate combustion in air with no other source of ignition. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

### TOXICOLOGICAL INFORMATION:

**Human and Animal Toxicology:** Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD<sub>50</sub>** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC<sub>50</sub>** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m<sup>3</sup>** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used.

**Other Information:** **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

### ECOLOGICAL INFORMATION:

EC is the effect concentration in water. **BCF** = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter. **TL<sub>m</sub>** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K<sub>ow</sub>** or **log K<sub>oc</sub>** and is used to assess a substance's behavior in the environment.

### REGULATORY INFORMATION:

**U.S. and CANADA:** **ACGIH:** American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA** or **Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration.